

KONİK BURÇ KAMA STANDART ÖLÇÜLERİ



KOD (Code)	DELİK ÇAPLARI (Bore Diameters)																H	TORK (Nm)	ÖLÇÜ	VİDA ADET (Pcs)
1008	9	10	11	12	14	16	18	19	20	22	24	25	-	-	-	-	22,3	136	1/4"	2
1108	9	10	11	12	14	16	18	19	20	22	24	25	28	-	-	-	22,3	147	1/4"	2
1210	12	14	16	18	19	20	22	24	25	28	30	-	-	-	-	-	25,4	407	3/8"	2
1610	14	16	18	19	20	22	24	25	28	30	32	35	38	40	-	-	25,4	486	3/8"	2
2012	18	19	20	22	24	25	28	30	32	35	38	40	42	45	48	50	31,8	808	7/16"	2
2517	20	22	24	25	28	30	32	35	38	40	42	45	48	50	55	60	44,5	1310	1/2"	2
3020	25	28	30	32	35	38	40	42	45	48	50	55	60	65	70	75	50,8	2710	5/8"	2
3030	25	28	30	32	35	38	40	42	45	48	50	55	60	65	70	75	76,2	2710	5/8"	2
3525	35	38	40	42	45	48	50	55	60	65	70	75	80	85	90	-	63,5	3800	1/2"	3
3535	35	38	40	42	45	48	50	55	60	65	70	75	80	85	90	-	88,9	5060	1/2"	3
4040	40	42	45	48	50	55	60	65	70	75	80	85	90	95	100	-	101,6	8740	5/8"	3
4545	45	48	50	55	60	65	70	75	80	85	90	95	100	110	-	-	114,3	12400	3/4"	3
5050	50	55	60	65	70	75	80	85	90	95	100	110	115	120	125	-	127	14200	7/8"	3
6050	70	75	80	85	90	95	100	110	115	120	125	130	140	150	-	-	127	31900	1 1/4"	3

KONİK BURÇ KAMA STANDART ÖLÇÜLERİ

D	B	T
10 -- 12	4	d+1,8
13 -- 17	5	d+2,3
18 -- 22	6	d+2,8
23 -- 30	8	d+3,3
31 -- 38	10	d+3,3
39 -- 44	12	d+3,3
45 -- 50	14	d+3,8
51 -- 58	16	d+4,3
59 -- 65	18	d+4,4
66 -- 75	20	d+4,9
76 -- 85	22	d+5,4
86 -- 95	25	d+5,4
96 -- 110	28	d+6,4
111 -- 130	32	d+7,4

